

3.2 LIMBACH L 2000 EA
3.2.1 Dimensions

Bore	: 90 mm
Stroke	: 78,4 mm
Displacement each Cyl.	: 498,5 cm ³
Total Displacement	: 1994 cm ³
Compression Ratio	: 8,6 : 1
Crankshaft Rotation	: counterclockwise
Magneto Timing	: 30° BTC
Firing Order	: 1-3-2-4

3.2.2 Equipment:

Magneto	: SLICK 4230, 4330 BENDIX S4RN21
Spark Plugs	: BOSCH WB 4 A (WB 240 ERT 1) EYQUEM A 755
Ignition Harness	: SLICK High-Temperature-Harness
Carburetor	: STROMBERG ZENITH 150 CD 3
Fuel Pump	: APG - LIMBACH
Alternator	: DUCCELLIER 14V-30A
Starter	: BOSCH 0.4 kW BOSCH 1.4 kW SJCE 0.4 kW SJCE 0.9 kW
Oil Pump	: Geared Pump
Oil Filter	: Oil Screen
Propeller Flange for EA 1	: 202.031.300
EA 2	: 202.031.320
EA 3	: 205.031.300

NOTE:

Preferred propellers:

Fixed-Pitch Propeller : Hoffmann HO11* / HO11A
: Mühlbauer MT

Variable-Pitch Propeller : Hoffmann HO-V62
: Mühlbauer MTV-1

By means of the adapter 202.032.320, the propeller flange for EA 1 may be used for fixed-pitch propellers for EA 2, too.